NSN 5996-01-442-8060



Video Amplifier - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5996-01-442-8060 **Overall Length:** 3.760 inches **Overall Height:** 0.450 inches **Overall Width:** 2.300 inches **Environmental Protection:** Explosion proof and fungus proof and moisture proof and shock resistant and vibration **Operating Tempurature Range:** -54.0/+95.0 degrees celsius Average Life Rating: 2000.0 **Average Life Measurement:** Hours **End Application:** Alr-56c lot 21 **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 70000.0 feet **Inclosure Type:** Hermetically sealed Installation Design: Mechanical **Circuit Construction Type:** Solid state Impedance Rating Per Channel: 100.000 ohms operating channel

Connection Type And Location:

Dish, sherbet threaded internal and dish, sherbet yoke and err-060 yoke

Connection Contact Type And Quantity:

2 hyperboloid drain and 3 tr int bs61 drain

External Dc Operating Voltage In Volts:

15.0 single voltage

Criticality Code Justification:

Feat

Special Features:

Drawing name-amplifier, log-videoand detector; 2 minute warm-up time; electrostatic discharge sensitive

Special Markings:

Esdc statement

Reference Number Differentiating Characteristics:

As differentiated by part number

NSN 5996-01-442-8060

Video Amplifier - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200