

View Online at <https://aerobasegroup.com/nsn/5996-01-464-6320>

Overall Length:

1.500 inches

Overall Height:

0.860 inches

Overall Width:

0.400 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

End Application:

Microcircuit, hybrid rfamplifier, 18876

Basic Shape Style:

Rectangular or square

Installation Design:

Mechanical

Circuit Construction Type:

Solid state

Frequency Per Channel:

3.5 gigahertz operating channel and 4.5 gigahertz operating channel

External Dc Operating Voltage In Volts:

22.0 single voltage

Test Data Document:

Mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And mil-prf-38535 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And mil-prf-38534 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And mil-a28875 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200

Mil-std (military Standard):

Mil-s-19500 spec