NSN 5996-01-587-2082

Synchro Signal Amplifier - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5996-01-587-2082 |
|--|
| Reliability Indicator: |
| Not established |
| nclosure Material: |
| Steel |
| Overall Length: |
| 3.100 inches |
| Overall Height: |
| 1.200 inches |
| Overall Width: |
| 5.100 inches |
| Operating Tempurature Range: |
| +32.0/+100.0 degrees fahrenheit |
| Fragility Factor: |
| Rugged |
| Storage Tempurature Range: |
| 20.0/+140.0 degrees fahrenheit |
| Average Life Measurement: |
| Not rated |
| End Application: |
| Ps/2 kvm extender |
| Basic Shape Style: |
| Rectangular or square |
| nclosure Type: |
| Encased |
| nstallation Design: |
| Free-standing and portable |
| Circuit Construction Type: |
| Solid state |
| Average Power Rating Per Channel: |
| 10.0 watts output |
| Operating Ac Frequency In Hertz: |
| 60.0 single voltage |
| External Ac Operating Voltage In Volts: |
| 120.0 single voltage |
| Product Name: |
| navy-amplifier, signal, ps/2kvm extender model |
| Special Features: |
| Supported features: kvm plus rs232; built-in surge protection, local and remote unit: 120vac at 60hz 9vdc 1.0a via ac adapters or 230vac |
| at 50hz 9vdc 1.5a via ac adapters |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5996-01-587-2082

Synchro Signal Amplifier - Page 2 of 2



Demilitarization:

No

Fiig:

A32200