

View Online at <https://aerobasegroup.com/nsn/5998-01-027-3643>

**Special Features:**

Aluminum case, yellow iridite fin. IAW MIL-C-5541 class 1a, 9.160 in. Lg, 2.625 in. W plus 20 pct, 1.260 in. H, i/o freq range 1.220 to 1.380 GHz, i/p power level to j2 plus 23 dBm PORM 1 dB, o/p power level w/power i/p plus 23 dBm to j1 plus 13 dBm PORM 2 dB, j3 plus 20 dBm plus 2 minus 3 dB, j4 plus 3 dBm PORM 2 dB, j5 plus 15 dBm PORM 2 dB, isolation j1 to j2 60 dB, j3 to j4 30 dB, j3 to j5 30 dB, detected o/p at j6 shall provide 0.050 to 0.100 VDC into 50 ohm load when i/p power into port j4 is plus 23 dBm, VSWR at ports j1 through j5 shall be 1.5 to 1 maximum when measured in 50 ohm system, coaxial connectors j1 through j6 shall be type SMA IAW MIL-C-39012, class 2, connector j8 power shall be IAW M24308/3-1; reference data, 1A1A4, TI-6340.8, instruction book, ARSR-3 system, FA-9200, part II, sec 8, vol 9, 8-76

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A511k0