

View Online at <https://aerobasegroup.com/nsn/5998-01-056-1965>

**Overall Length:**

5.500 inches

**Overall Width:**

4.000 inches

**Special Features:**

Insulative mounting pads and supporting connector plug shall be free of conformal coating; major components: capacitors 5, resistors 3, microcircuits 12, indicator lamps 10, connector plug 1, connector testpoint mounted on a common printed wiring board 1; mounting configuration: slide-in, plug-in printed circuit board with two thumb-depress, top mounted ejectors; special test features: standard test conditions referenced herein are as follows: temperature 25 degrees c porm 10 degrees c relative humidi type 90 per cent atmospheric pressure 23.22 to 31.42 inches of mercury. Calibration of all test equipment shall be i.A.W. Mil-c-45662. Drawing engineering tolerances are absolute unless otherwise specified

**Test Data Document:**

81349-mil-p-46843 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A511k0