

View Online at <https://aerobasegroup.com/nsn/5998-01-122-1071>

**General Description:**

This flexible circuit shall conform to mil-p-50884b type b class 2, trim configuration controlled by artwork master outline shall be within plus or minus .015 of artwork with no copper remaining in border, copper plate holes with pads on both sides .001 to .0015 per mil-c-14550, coverlay .001 thk polyamide per mil-p-46112 type 1 with .002 thk acrylic adhesive, base .001 thk polyamide per mil-p-46112 type 1 with .001 thk acrylic adhesive two sides, foil 1 oz rolled annealed copper per mil-f-55561 type ii, underlay .001 thk polyamide per mil-p-46112 type 1 with .002 thk acrylic adhesive, hole a coverlay .045 base copper clad .035 underlay .065 q type 61 diameter tol plus or minus .003, hole a1 coverlay .045 base copper clad .035 underlay .045 q type 78 diameter tol plus or minus .003, hole b coverlay .060 base copper clad .050 underlay .060q type 30 diameter tol plus or minus .003, hole c coverlay .065 base copper clad .030 underlay .040 q type 64 diameter tol plus or minus .003

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli