

View Online at <https://aerobasegroup.com/nsn/5999-00-003-3515>

Thread Class:

2b

Thread Pitch Diameters:

+0.1000/+0.1001 inches

Body Style:

Rectangular, w/shaft

Overall Depth:

4.800 inches

Body Length:

1.250 inches

Body Width:

0.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

4.209 inches

Shortest Horizontal Distance Between Mounting Centers:

1.600 inches

Longest Vertical Distance Between Mounting Centers:

0.890 inches

Operating Temperature Range:

-28.0/+80.0 degrees celsius

Mounting Facility Quantity:

3

Voltage Rating:

1.000 pounds per hour dry and 75.000 pounds per hour with retaining chain

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Body Depth:

4.500 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Isosceles triangle

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

500.000 nanoseconds single section

Segment Quantity Per Section:

2 single section

Distance From End Of Body To Center Of Shaft:

0.990 inches

Distance From Bottom Of Body To Center Of Shaft:

0.250 inches

Terminal Type And Quantity:

4 tab solder lug

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100