

View Online at <https://aerobasegroup.com/nsn/5999-00-003-3560>

Thread Class:

2b

Thread Pitch Diameters:

+0.1177 to 0.1214 inches

Body Style:

Rectangular, bracketed

Overall Length:

4.688 inches

Body Length:

3.625 inches

Body Width:

4.250 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.000 inches

Operating Temperature Range:

-5.0 to 75.0 degrees celsius

Mounting Facility Quantity:

2

Material And Location:

Copper terminal or nickel-copper alloy, qq-n-281, class a terminal

Surface Treatment And Location:

Paint case

Input Impedance Rating:

1.500 kilohms

Frequency Bandwidth:

Between 1.0 kilohertz and 6.0 kilohertz

Body Depth:

2.375 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

20.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

361.100 microseconds single section

Segment Quantity Per Section:

14 single section

Segment Delay Time:

7.000 microseconds single section 15th segment

Terminal Type And Quantity:

19 pin

Special Features:

Nineteen irregularly spaced terminals

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100