Electronic Shielding Gasket - Page 1 of 2





| Cross Sectional Shape: |
|---|
| Emi |
| Hole Diameter: |
| 0.310 inches |
| Overall Length: |
| 7.560 inches |
| Tempurature Rating: |
| -54.0 degrees celsius and 232.0 degrees celsius |
| Overall Width: |
| 4.560 inches |
| Inside Corner Radius: |
| 0.250 inches |
| Outside Corner Radius: |
| 0.250 inches |
| Aperture Width: |
| 3.560 inches |
| Aperture Length: |
| 6.560 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 2.790 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.250 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.250 inches |
| Cross-sectional Height: |
| 0.062 inches |
| Bolt Hole Quantity: |
| 8 |
| Environmental Protection Material Location: |
| Throughout rf shielding gasket |
| Material: |
| Rubber silicone class q environmental seal |
| Material Specification: |
| Zz-r-765, class 3 federal specification single material response environmental seal |
| Style Designator: |
| Non-circular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5999-00-007-7913 Electronic Shielding Gasket - Page 2 of 2

Fiig: A032a0

