

View Online at <https://aerobasegroup.com/nsn/5999-00-011-4997>

Body Style:

Rectangular

Hole Diameter:

0.187 inches

Body Length:

3.500 inches

Body Width:

0.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.187 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Mounting Facility Quantity:

2

Voltage Rating:

600.000 pounds per hour with retaining chain

Material And Location:

Plastic, epoxy resin case

Surface Treatment And Location:

Any acceptable case

Input Impedance Rating:

1.000 kilohms

Output Impedance Rating:

1.000 kilohms

Frequency Bandwidth:

18000.0 kilohertz

Body Depth:

0.500 inches

Mounting Facility:

Unthreaded hole

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

0.540

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Variable

Section Delay Time:

300.000 milliseconds single section

Delay Time Variation Per Deg Celsius:

150.000 microseconds

Pulse Rise Time Rating:

0.02 microseconds

Terminal Type And Quantity:

3 wire hook

Test Data Document:

94117-292014+1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100