

View Online at <https://aerobasegroup.com/nsn/5999-00-011-4997>

**Body Style:**

Rectangular

**Hole Diameter:**

0.187 inches

**Body Length:**

3.500 inches

**Body Width:**

0.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

3.187 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Mounting Facility Quantity:**

2

**Voltage Rating:**

600.000 pounds per hour with retaining chain

**Material And Location:**

Plastic, epoxy resin case

**Surface Treatment And Location:**

Any acceptable case

**Input Impedance Rating:**

1.000 kilohms

**Output Impedance Rating:**

1.000 kilohms

**Frequency Bandwidth:**

18000.0 kilohertz

**Body Depth:**

0.500 inches

**Mounting Facility:**

Unthreaded hole

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

0.540

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

300.000 milliseconds single section

**Delay Time Variation Per Deg Celsius:**

150.000 microseconds

**Pulse Rise Time Rating:**

0.02 microseconds

**Terminal Type And Quantity:**

3 wire hook

**Test Data Document:**

94117-292014+1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100