NSN 5999-00-011-9694



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-011-9694 **Thread Class:** 2a **Thread Pitch Diameters:** +0.1437 to 0.1475 inches **Body Style:** Rectangular **Body Length:** 3.844 inches **Body Width:** 1.688 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.812 inches **Operating Tempurature Range:** +0.0 to 65.0 degrees celsius Stud Length: 0.406 inches **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 2 **Material And Location:** Metal case **Surface Treatment And Location:** Varnish case **Output Impedance Rating:** 75.000 ohms **Body Depth:** 1.688 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** 2 position in-line **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped **Section Delay Time:**

0.370 microseconds single section **Segment Quantity Per Section:**

5 single section

NSN 5999-00-011-9694

Delay Line - Page 2 of 2



Segment Delay Time:

0.190 microseconds single section 1st segment

Terminal Type And Quantity:

7 turret

Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100