# NSN 5999-00-011-9694

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-011-9694

Thread	Class:

2a

**Thread Pitch Diameters:** 

+0.1437 to 0.1475 inches

## Body Style:

Rectangular

## **Body Length:**

3.844 inches

#### **Body Width:**

1.688 inches

Individual Section Quantity:

1

#### Longest Horizontal Distance Between Mounting Centers:

0.812 inches

#### **Operating Tempurature Range:**

+0.0 to 65.0 degrees celsius

#### Stud Length:

0.406 inches

# Inclosure Type:

Hermetically sealed

## Mounting Facility Quantity:

2

### Material And Location:

Metal case

### Surface Treatment And Location:

Varnish case

### **Output Impedance Rating:**

75.000 ohms

### Body Depth:

1.688 inches

### **Mounting Facility:**

Threaded stud

### Mounting Provision Arrangement Style:

2 position in-line

### Signal Delay Method:

Lumped constant

## **Delay Time Variation Method:**

Tapped

#### Section Delay Time:

0.370 microseconds single section

# Segment Quantity Per Section:

5 single section

# NSN 5999-00-011-9694

Delay Line - Page 2 of 2



Segment Delay Time:

0.190 microseconds single section 1st segment

## Terminal Type And Quantity:

7 turret

# Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A32100