NSN 5999-00-015-3493



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-015-3493 **Thread Class:** 2b **Thread Pitch Diameters:** +0.1875 to 0.1876 inches **Body Style:** Rectangular **Adjustment Device Quantity: Adjustment Device Drive Type:** Slotted screw **Body Length:** 4.875 inches **Body Width:** 0.438 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 3.375 inches **Longest Vertical Distance Between Mounting Centers:** 3.250 inches **Operating Tempurature Range:** +0.0 to 65.0 degrees celsius **Mounting Facility Quantity: Material And Location:** Aluminum alloy case **Surface Treatment And Location:** Anodized, mil-a-8625, type 1 case **Body Depth:** 4.250 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Signal Delay Method:** Inductance **Delay Time Variation Method:** Variable **Section Delay Time:**

704.800 nanoseconds single section

Terminal Type And Quantity:

5 wire hook

NSN 5999-00-015-3493

Delay Line - Page 2 of 2



Thread Size And Series/type Designato	r:
---------------------------------------	----

0.138-32 unc

Fsc Application Data:

Sonar set

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32100