NSN 5999-00-015-4346

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-015-4346 **Thread Class:** 2b **Thread Pitch Diameters:** +0.0997 to 0.1177 inches **Body Style:** Rectangular, front connection **Overall Depth:** 3.312 inches **Body Length:** 4.425 inches **Body Width:** 1.925 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 3.125 inches **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 4 **Voltage Rating:** 6.000 volts **Material And Location:** Steel case **Surface Treatment And Location:** Tin plate case Input Impedance Rating: 300.000 ohms **Output Impedance Rating:** 300.000 ohms **Body Depth:** 2.812 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** 2 position in-line

Inductance

Delay Time Variation Method:

Signal Delay Method:

Tapped

NSN 5999-00-015-4346Delay Line - Page 2 of 2



Section Delay Time:
61.800 microseconds single section
Segment Quantity Per Section:
13 single section
Segment Delay Time:
8.700 microseconds single section 13th segment
Delay Time Variation Per Deg Celsius:
0.025 microseconds
Pulse Rise Time Rating:
0.24 microseconds
Terminal Type And Quantity:
1 coaxial receptacle
Thread Size And Series/type Designator:
0.138-32 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

Fiig: A32100