

View Online at <https://aerobasegroup.com/nsn/5999-00-015-4346>

Thread Class:

2b

Thread Pitch Diameters:

+0.0997 to 0.1177 inches

Body Style:

Rectangular, front connection

Overall Depth:

3.312 inches

Body Length:

4.425 inches

Body Width:

1.925 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.125 inches

Operating Temperature Range:

-55.0 to 125.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4

Voltage Rating:

6.000 volts

Material And Location:

Steel case

Surface Treatment And Location:

Tin plate case

Input Impedance Rating:

300.000 ohms

Output Impedance Rating:

300.000 ohms

Body Depth:

2.812 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

2 position in-line

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

61.800 microseconds single section

Segment Quantity Per Section:

13 single section

Segment Delay Time:

8.700 microseconds single section 13th segment

Delay Time Variation Per Deg Celsius:

0.025 microseconds

Pulse Rise Time Rating:

0.24 microseconds

Terminal Type And Quantity:

1 coaxial receptacle

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100