NSN 5999-00-016-0550

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-016-0550

Thread Class:
2b
Thread Pitch Diameters:
+0.1196 to 0.1197 inches
Body Style:
Round w/square base
Overall Depth:
4.000 inches
Overall Length:
22.000 inches
Overall Width:
23.100 inches
Body Diameter:
21.500 inches
Mounting Hole Circle Radius:
10.190 inches
Frequency Rating:
20.000 megahertz
Individual Section Quantity:
3
Operating Tempurature Range:
+0.0 to 50.0 degrees celsius
Mounting Facility Quantity:
6
Material And Location:
Steel case
Surface Treatment And Location:
Enamel, dull gray, metallic case
Input Impedance Rating:
95.000 ohms
Output Impedance Rating:
95.000 ohms
Frequency Bandwidth:
4000.0 kilohertz
Body Depth:
3.875 inches
Mounting Facility:
Threaded hole
Mounting Provision Arrangement Style:
Four position circular
Attenuation In Decibels:

53.000

NSN 5999-00-016-0550

Delay Line - Page 2 of 2

A32100



Signal Delay Method:
Inductance
Section Delay Time:
4.815 milliseconds 1st section
Terminal Type And Quantity:
7 coaxial receptacle
Thread Size And Series/type Designator:
0.250-20 unc
Fsc Application Data:
Radar nonairborne except fire control and guided missile
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: