

View Online at <https://aerobasegroup.com/nsn/5999-00-018-6718>

Body Style:

Rectangular

Slot Depth:

0.062 inches

Slot Width:

0.031 inches

Shaft Diameter:

0.094 inches

Shaft Length:

0.120 inches

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Shaft

Body Length:

2.250 inches

Body Width:

0.350 inches

Shaft Style:

Round, slotted

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.800 inches

Longest Vertical Distance Between Mounting Centers:

0.300 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Mounting Facility Quantity:

4

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

200.000 ohms

Output Impedance Rating:

200.000 ohms

Frequency Bandwidth:

27000.0 kilohertz

Body Depth:

0.750 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

0.500

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

Section Delay Time:

1.500 nanoseconds single section and 50.000 nanoseconds single section

Pulse Rise Time Rating:

13.0 nanoseconds

Terminal Type And Quantity:

4 pin

Fsc Application Data:

Except testing, multiapplication

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100