

View Online at <https://aerobasegroup.com/nsn/5999-00-019-0139>

**Thread Class:**

2a

**Body Style:**

Rectangular

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Shaft

**Body Length:**

4.500 inches

**Body Width:**

4.500 inches

**Shaft Style:**

Round, slotted

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

3.500 inches

**Longest Vertical Distance Between Mounting Centers:**

3.500 inches

**Operating Temperature Range:**

-5.0 to 65.0 degrees celsius

**Mounting Facility Quantity:**

4

**Input Impedance Rating:**

75.000 ohms

**Output Impedance Rating:**

75.000 ohms

**Body Depth:**

1.125 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

3.000

**Delay Time Variation Method:**

Adjustable

**Section Delay Time:**

9.500 microseconds single section

**Pulse Rise Time Rating:**

100.0 nanoseconds

**Terminal Type And Quantity:**

4 wire hook

**Thread Size And Series/type Designator:**

0.164-32 unc

**Fsc Application Data:**

Radar set, guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100