NSN 5999-00-019-0139

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-019-0139 **Thread Class:** 2a **Body Style:** Rectangular **Adjustment Device Quantity: Adjustment Device Drive Type:** Shaft **Body Length:** 4.500 inches **Body Width:** 4.500 inches **Shaft Style:** Round, slotted **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 3.500 inches **Longest Vertical Distance Between Mounting Centers:** 3.500 inches **Operating Tempurature Range:** -5.0 to 65.0 degrees celsius **Mounting Facility Quantity:** Input Impedance Rating: 75.000 ohms **Output Impedance Rating:** 75.000 ohms **Body Depth:** 1.125 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 3.000 **Delay Time Variation Method:** Adjustable

9.500 microseconds single section **Pulse Rise Time Rating:**

Section Delay Time:

100.0 nanoseconds

NSN 5999-00-019-0139

Delay Line - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

4 wire hook

Thread Size And Series/type Designator:

0.164-32 unc

Fsc Application Data:

Radar set, guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100