

View Online at <https://aerobasegroup.com/nsn/5999-00-020-6159>

Body Style:

Rectangular, w/shaft

Overall Depth:

3.930 inches

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Slotted screw

Body Length:

3.750 inches

Body Width:

3.750 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.250 inches

Longest Vertical Distance Between Mounting Centers:

3.250 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4

Voltage Rating:

20.000 volts

Material And Location:

Steel case

Surface Treatment And Location:

Tin plate case

Input Impedance Rating:

250.000 ohms

Output Impedance Rating:

250.000 ohms

Body Depth:

3.120 inches

Step Quantity:

15

Mounting Facility:

Threaded insert

Mounting Provision Arrangement Style:

Four position rectangular

Signal Delay Method:

Inductance

Delay Time Variation Method:

Adjustable

Delay Time Per Step:

Between 0.041 nanoseconds and 4.070 nanoseconds

Section Delay Time:

12.200 nanoseconds single section

Segment Quantity Per Section:

15 single section

Segment Delay Time:

4.070 nanoseconds single section 14th segment

Pulse Rise Time Rating:

4.0 nanoseconds

Distance From End Of Body To Center Of Shaft:

1.875 inches

Distance From Bottom Of Body To Center Of Shaft:

1.625 inches

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100