## NSN 5999-00-023-2257



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-023-2257 **Thread Class:** 2b **Body Style:** Rectangular, top connection **Overall Width:** 2.000 inches **Body Length:** 7.125 inches **Body Width:** 1.688 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 7.125 inches **Longest Vertical Distance Between Mounting Centers:** 2.188 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Stud Length: 0.250 inches **Mounting Facility Quantity:** 4 Input Impedance Rating: 180.000 ohms **Output Impedance Rating:** 180.000 ohms **Body Depth:** 2.188 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 6.000 **Delay Time Variation Method: Tapped Section Delay Time:** 27.000 microseconds single section

27 single section

**Pulse Rise Time Rating:** 

**Segment Quantity Per Section:** 

0.1 microseconds

## NSN 5999-00-023-2257

Delay Line - Page 2 of 2



Terminal	<b>Type</b>	And	Quantity	y:
----------	-------------	-----	----------	----

30 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100