# NSN 5999-00-023-2257

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-023-2257

## Thread Class:

2b

### **Body Style:**

Rectangular, top connection

## **Overall Width:**

2.000 inches

#### **Body Length:**

7.125 inches

#### **Body Width:**

1.688 inches

#### Individual Section Quantity:

1

#### Longest Horizontal Distance Between Mounting Centers:

7.125 inches

#### Longest Vertical Distance Between Mounting Centers:

2.188 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Stud Length:

0.250 inches

## **Mounting Facility Quantity:**

4

## Input Impedance Rating:

180.000 ohms

#### **Output Impedance Rating:**

180.000 ohms

#### **Body Depth:**

2.188 inches

#### **Mounting Facility:**

Threaded stud

#### Mounting Provision Arrangement Style:

Four position rectangular

#### Attenuation In Decibels:

6.000

#### **Delay Time Variation Method:**

Tapped

#### Section Delay Time:

27.000 microseconds single section

## Segment Quantity Per Section:

27 single section

### Pulse Rise Time Rating:

0.1 microseconds

# NSN 5999-00-023-2257

Delay Line - Page 2 of 2



## Terminal Type And Quantity:

30 wire hook

## Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

Fiig:

A32100