

View Online at <https://aerobasegroup.com/nsn/5999-00-025-9307>

Body Style:

Rectangular

Frequency Rating:

30.000 hertz

Body Length:

1.875 inches

Body Width:

1.625 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.437 inches

Longest Vertical Distance Between Mounting Centers:

1.187 inches

Operating Temperature Range:

+0.0/+60.0 degrees celsius

Stud Length:

0.375 inches

Mounting Facility Quantity:

4

Voltage Rating:

6.000 pounds per hour wet

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Body Depth:

2.375 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

6.000

Signal Delay Method:

Electromechanical

Section Delay Time:

21.800 microseconds single section

Delay Time Variation Per Deg Celsius:

0.050 microseconds

Pulse Rise Time Rating:

1.0 microseconds

Terminal Type And Quantity:

3 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100