## NSN 5999-00-025-9308



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-025-9308 **Body Style:** Rectangular Frequency Rating: 30.000 hertz **Body Length:** 1.625 inches **Body Width:** 1.000 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.312 inches **Longest Vertical Distance Between Mounting Centers:** 0.750 inches **Operating Tempurature Range:** +0.0/+60.0 degrees celsius Stud Length: 0.375 inches **Mounting Facility Quantity: Voltage Rating:** 6.000 pounds per hour wet Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms **Body Depth:** 2.437 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 6.000 **Signal Delay Method:** Electromechanical **Section Delay Time:** 18.800 microseconds single section **Delay Time Variation Per Deg Celsius:** 

0.050 microseconds

Pulse Rise Time Rating:

1.0 microseconds

## NSN 5999-00-025-9308

Delay Line - Page 2 of 2



Terminal Type And Quantity	Terminal	<b>Type</b>	And	Quantity	<b>/</b> :
----------------------------	----------	-------------	-----	----------	------------

3 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A32100