NSN 5999-00-031-0613

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-031-0613

| noie Diameter: |
|---|
| 0.166 inches |
| Individual Section Quantity: |
| 1 |
| Longest Horizontal Distance Between Mounting Centers: |
| 7.125 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 0.750 inches |
| Operating Tempurature Range: |
| -54.0/+11.0 degrees celsius |
| Mounting Facility Quantity: |
| 4 |
| Material And Location: |
| Brass case |
| Surface Treatment And Location: |
| Painted case |
| Input Impedance Rating: |
| 560.000 ohms |
| Output Impedance Rating: |
| 560.000 ohms |
| Frequency Bandwidth: |
| 580.0 kilohertz |
| Mounting Facility: |
| Unthreaded hole |
| Mounting Provision Arrangement Style: |
| Four position rectangular |
| Attenuation In Decibels: |
| 2.000 |
| Signal Delay Method: |
| Transmission line |
| Delay Time Variation Method: |
| Tapped |
| Section Delay Time: |
| 8.060 microseconds single section |
| Terminal Type And Quantity: |
| 5 tab solder lug |
| Fsc Application Data: |
| Coder, synchronizer radar recognition set |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5999-00-031-0613

Delay Line - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32100