

View Online at <https://aerobasegroup.com/nsn/5999-00-031-0613>

**Hole Diameter:**

0.166 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

7.125 inches

**Longest Vertical Distance Between Mounting Centers:**

0.750 inches

**Operating Temperature Range:**

-54.0/+11.0 degrees celsius

**Mounting Facility Quantity:**

4

**Material And Location:**

Brass case

**Surface Treatment And Location:**

Painted case

**Input Impedance Rating:**

560.000 ohms

**Output Impedance Rating:**

560.000 ohms

**Frequency Bandwidth:**

580.0 kilohertz

**Mounting Facility:**

Unthreaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

2.000

**Signal Delay Method:**

Transmission line

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

8.060 microseconds single section

**Terminal Type And Quantity:**

5 tab solder lug

**Fsc Application Data:**

Coder, synchronizer radar recognition set

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100