NSN 5999-00-035-8883

Electrical Contact - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-035-8883

| | Thread Class: |
|---|---------------------------------|
| 2 | 2b |
| ٦ | Thread Direction: |
| F | Right-hand |
| 0 | Overall Length: |
| 1 | .625 inches |
| 0 | Overall Diameter: |
| С | 0.250 inches |
| Ν | Nounting Facility Quantity: |
| 1 | |
| ١ | /oltage Rating In Volts: |
| 2 | 230.0 dc |
| (| Current Rating In Amps: |
| 1 | 80.0 |
| N | Nounting Method: |
| 1 | Threaded hole |
| 1 | Fhready Qty Per Inch (tpi): |
| 3 | 32 |
| 1 | Thread Size: |
| С | 0.138 inches |
| Ν | Naterial: |
| (| Copper alloy body and contact |
| F | Precious Material And Location: |
| (| Contact surface silver |
| F | Precious Material And Weight: |
| С | 0.005 silver grains, troy |
| F | Precious Material: |
| S | Silver |
| S | Surface Treatment: |
| S | Silver contact |
| S | Style Designator: |
| (| Cylindrical shape |
| 1 | Thread Series Designator: |
| ι | Jnc |
| 1 | Ferminal Type And Quantity: |
| 1 | threaded hole center |
| S | Shelf Life: |
| ٢ | l/a |
| ι | Jnit Of Measure: |

No

NSN 5999-00-035-8883

Electrical Contact - Page 2 of 2

Fiig: A222a0

