

View Online at <https://aerobasegroup.com/nsn/5999-00-052-6231>

Thread Class:

1a

Thread Pitch Diameters:

+0.0610 to 0.0611 inches

Body Style:

Rectangular

Body Length:

3.500 inches

Body Width:

3.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.750 inches

Longest Vertical Distance Between Mounting Centers:

2.750 inches

Operating Temperature Range:

-40.0 to 80.0 degrees celsius

Stud Length:

0.375 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4

Voltage Rating:

Between 150.000 volts and 300.000 volts

Body Depth:

0.750 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

3.000

Signal Delay Method:

Transmission line

Delay Time Variation Method:

Tapped

Section Delay Time:

32.000 microseconds single section

Segment Quantity Per Section:

6 single section

Segment Delay Time:

9.200 microseconds - single section 3rd segment

Pulse Rise Time Rating:

2.5 microseconds

Terminal Type And Quantity:

8 wire leads

Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100