

View Online at <https://aerobasegroup.com/nsn/5999-00-057-8537>

Body Style:

Rectangular

Hole Diameter:

0.140 inches

Frequency Rating:

96.000 megahertz

Body Length:

5.500 inches

Body Width:

2.625 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

6.000 inches

Longest Vertical Distance Between Mounting Centers:

1.125 inches

Mounting Facility Quantity:

4

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

1.500 kilohms

Output Impedance Rating:

1.500 kilohms

Frequency Bandwidth:

55000.0 kilohertz

Body Depth:

0.875 inches

Mounting Facility:

Unthreaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

3.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

10.000 microseconds single section

Segment Quantity Per Section:

2 single section

Segment Delay Time:

5.000 microseconds single section all segments

Terminal Type And Quantity:

4 tab solder lug

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100