## NSN 5999-00-061-7864



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-061-7864 **Body Style:** Rectangular **Body Length:** 3.000 inches **Body Width:** 0.750 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.400 inches **Longest Vertical Distance Between Mounting Centers:** 0.500 inches **Operating Tempurature Range:** -62.0/+85.0 degrees celsius **Mounting Facility Quantity: Voltage Rating:** 50.000 volts **Material And Location:** Copper case **Surface Treatment And Location:** Lead case Input Impedance Rating: 50.000 ohms **Output Impedance Rating:** 50.000 ohms **Body Depth:** 0.500 inches **Mounting Facility:** Pin **Mounting Provision Arrangement Style:** Four position rectangular **Signal Delay Method:** Lumped constant **Delay Time Variation Method: Tapped Section Delay Time:** 500.000 nanoseconds single section

Pulse Rise Time Rating: 10.0 nanoseconds

**Terminal Type And Quantity:** 

6 pin

## NSN 5999-00-061-7864

Delay Line - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100