

View Online at <https://aerobasegroup.com/nsn/5999-00-063-9230>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1875 to 0.1876 inches

**Body Style:**

Rectangular

**Body Length:**

1.360 inches

**Body Width:**

4.000 inches

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

0.781 inches

**Longest Vertical Distance Between Mounting Centers:**

0.906 inches

**Operating Temperature Range:**

+0.0 to 60.0 degrees celsius

**Stud Length:**

0.375 inches

**Mounting Facility Quantity:**

4

**Material And Location:**

Any acceptable

**Input Impedance Rating:**

400.000 ohms

**Output Impedance Rating:**

400.000 ohms

**Body Depth:**

1.110 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

2.000

**Signal Delay Method:**

Inductance

**Section Delay Time:**

7.000 microseconds 1st section

**Pulse Rise Time Rating:**

0.5 microseconds

**Terminal Type And Quantity:**

7 wire hook

**Thread Size And Series/type Designator:**

0-138-32 unc

**Fsc Application Data:**

Radar nonairborne except fire control and guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100