

View Online at <https://aerobasegroup.com/nsn/5999-00-063-9230>

Thread Class:

2a

Thread Pitch Diameters:

+0.1875 to 0.1876 inches

Body Style:

Rectangular

Body Length:

1.360 inches

Body Width:

4.000 inches

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

0.781 inches

Longest Vertical Distance Between Mounting Centers:

0.906 inches

Operating Temperature Range:

+0.0 to 60.0 degrees celsius

Stud Length:

0.375 inches

Mounting Facility Quantity:

4

Material And Location:

Any acceptable

Input Impedance Rating:

400.000 ohms

Output Impedance Rating:

400.000 ohms

Body Depth:

1.110 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

2.000

Signal Delay Method:

Inductance

Section Delay Time:

7.000 microseconds 1st section

Pulse Rise Time Rating:

0.5 microseconds

Terminal Type And Quantity:

7 wire hook

Thread Size And Series/type Designator:

0-138-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100