

View Online at <https://aerobasegroup.com/nsn/5999-00-065-5890>

Thread Class:

2a

Body Style:

Rectangular, top connection

Overall Width:

1.750 inches

Body Length:

4.000 inches

Body Width:

1.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.000 inches

Longest Vertical Distance Between Mounting Centers:

3.500 inches

Operating Temperature Range:

+0.0 to 75.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

6.000 volts

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Output Impedance Rating:

1.000 kilohms

Body Depth:

1.500 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

1.500

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

8.600 microseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

860.000 nanoseconds single section 1st segment

Pulse Rise Time Rating:

350.0 nanoseconds

Terminal Type And Quantity:

12 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100