

View Online at <https://aerobasegroup.com/nsn/5999-00-065-5890>

**Thread Class:**

2a

**Body Style:**

Rectangular, top connection

**Overall Width:**

1.750 inches

**Body Length:**

4.000 inches

**Body Width:**

1.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.000 inches

**Longest Vertical Distance Between Mounting Centers:**

3.500 inches

**Operating Temperature Range:**

+0.0 to 75.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

6.000 volts

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Any acceptable

**Output Impedance Rating:**

1.000 kilohms

**Body Depth:**

1.500 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

1.500

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

8.600 microseconds single section

**Segment Quantity Per Section:**

10 single section

**Segment Delay Time:**

860.000 nanoseconds single section 1st segment

**Pulse Rise Time Rating:**

350.0 nanoseconds

**Terminal Type And Quantity:**

12 wire hook

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100