## NSN 5999-00-070-9545



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-070-9545 **Thread Class:** 2b **Thread Pitch Diameters:** +0.1875/+0.1876 inches **Body Style:** Rectangular **Body Length:** 6.000 inches **Body Width:** 2.000 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 5.000 inches **Operating Tempurature Range:** -54.0/+80.0 degrees celsius **Mounting Facility Quantity:** 4 **Voltage Rating:** 100.000 volts **Material And Location:** Any acceptable **Surface Treatment And Location:** Enamel, dull gray, metallic body Input Impedance Rating: 9.100 kilohms **Output Impedance Rating:** 9.100 kilohms Frequency Bandwidth: 360.0 kilohertz **Body Depth:** 1.000 inches **Mounting Facility: Mounting Provision Arrangement Style:** 

Threaded hole 2 position in-line **Attenuation In Decibels:** 1.000 **Signal Delay Method:** 

Inductance

**Section Delay Time:** 

12.000 microseconds single section

## NSN 5999-00-070-9545

Delay Line - Page 2 of 2



Pulse Rise	Time	Rating:
------------	------	---------

1.0 microseconds

**Terminal Type And Quantity:** 

3 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

**Fsc Application Data:** 

Radio navigation nonairborne

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100