## NSN 5999-00-070-9547



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-070-9547 **Body Style:** Rectangular, front connection **Overall Depth:** Between 2.438 inches and 2.562 inches **Adjustment Device Quantity: Adjustment Device Drive Type:** Linear slide **Body Width:** Between 2.719 inches and 2.781 inches **Individual Section Quantity:** 4 **Longest Horizontal Distance Between Mounting Centers:** Between 7.609 inches and 7.641 inches **Longest Vertical Distance Between Mounting Centers:** 2.188 inches **Operating Tempurature Range:** -54.0 to 80.0 degrees celsius **Mounting Facility Quantity: Material And Location:** Metal Input Impedance Rating: 8.200 kilohms **Output Impedance Rating:** 8.200 kilohms Frequency Bandwidth: 250.0 kilohertz **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** Four position rectangular **Delay Time Variation Method:** Adjustable **Section Delay Time:** 7.500 microseconds 1st section **Terminal Type And Quantity:** 7 solder stud Thread Size And Series/type Designator: 0.190-32 unf

N/a

Shelf Life:

## NSN 5999-00-070-9547

Delay Line - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100