## NSN 5999-00-070-9547

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-070-9547

## Body Style:

Rectangular, front connection

### Overall Depth:

Between 2.438 inches and 2.562 inches

## Adjustment Device Quantity:

3

#### Adjustment Device Drive Type:

Linear slide

#### Body Width:

Between 2.719 inches and 2.781 inches

#### Individual Section Quantity:

4

#### Longest Horizontal Distance Between Mounting Centers:

Between 7.609 inches and 7.641 inches

#### Longest Vertical Distance Between Mounting Centers:

2.188 inches

#### **Operating Tempurature Range:**

-54.0 to 80.0 degrees celsius

#### **Mounting Facility Quantity:**

4

#### Material And Location:

Metal

#### Input Impedance Rating:

8.200 kilohms

#### **Output Impedance Rating:**

8.200 kilohms

#### Frequency Bandwidth:

250.0 kilohertz

#### **Mounting Facility:**

Threaded stud

#### Mounting Provision Arrangement Style:

Four position rectangular

#### **Delay Time Variation Method:**

Adjustable

#### Section Delay Time:

7.500 microseconds 1st section

#### Terminal Type And Quantity:

7 solder stud

#### Thread Size And Series/type Designator:

0.190-32 unf

#### Shelf Life:

N/a

# NSN 5999-00-070-9547

Delay Line - Page 2 of 2

Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

Fiig:

A32100

