NSN 5999-00-070-9548



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-070-9548 **Thread Class:** 2b **Body Style:** Rectangular **Body Length:** 2.000 inches **Body Width:** 1.875 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.375 inches **Longest Vertical Distance Between Mounting Centers:** 1.375 inches **Operating Tempurature Range:** -54.0/+80.0 degrees celsius **Mounting Facility Quantity:** 4 **Voltage Rating:** 200.000 volts **Material And Location:** Any acceptable **Surface Treatment And Location:** Enamel, dull gray, metallic body Input Impedance Rating: 2.000 kilohms **Output Impedance Rating:** 2.000 kilohms Frequency Bandwidth: 3600.0 kilohertz **Body Depth:** 1.063 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 1.000

Signal Delay Method: Inductance

Section Delay Time:

750.000 nanoseconds single section

NSN 5999-00-070-9548

Delay Line - Page 2 of 2



Pulse Rise Time Rating:
100.0 nanoseconds
Terminal Type And Quantity:
3 pin
Thread Size And Series/type Designator:
0.138-32 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A32100