NSN 5999-00-071-8162

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-071-8162 **Thread Class:** 2b **Thread Pitch Diameters:** +0.0250 to 0.0251 inches **Body Style:** Rectangular, front connection **Overall Depth:** 1.187 inches **Body Length:** 5.332 inches **Body Width:** 1.208 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** Between 3.209 inches and 3.229 inches **Operating Tempurature Range:** -40.0 to 175.0 degrees fahrenheit **Mounting Facility Quantity:** Voltage Rating: 50.000 volts **Material And Location:** Any acceptable Input Impedance Rating: 100.000 ohms **Body Depth:** 1.000 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** 4.000 **Signal Delay Method:** Electromechanical **Delay Time Variation Method:** Tapped **Section Delay Time:**

2.420 microseconds single section

Segment Quantity Per Section:

5 single section

NSN 5999-00-071-8162

Delay Line - Page 2 of 2



Segment De	elay Time:
------------	------------

1.100 microseconds single section 5th segment

Pulse Rise Time Rating:

220.0 nanoseconds

Terminal Type And Quantity:

8 tab solder lug

Special Features:

Markings, include vendors name, part number and major technical values

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32100