

View Online at <https://aerobasegroup.com/nsn/5999-00-076-2117>

Thread Class:

2a

Thread Pitch Diameters:

+0.2500/+0.2501 inches

Body Style:

Rectangular

Body Length:

2.250 inches

Body Width:

3.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.500 inches

Longest Vertical Distance Between Mounting Centers:

1.375 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Stud Length:

0.469 inches

Mounting Facility Quantity:

4

Material And Location:

Any acceptable

Surface Treatment And Location:

Enamel, mil-e-15090, type 3, class 1 case

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Frequency Bandwidth:

1800.0 kilohertz

Body Depth:

2.130 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

2.000

Signal Delay Method:

Inductance

Section Delay Time:

4.500 microseconds single section

Pulse Rise Time Rating:

50.0 nanoseconds

Terminal Type And Quantity:

2 coaxial receptacle

Thread Size And Series/type Designator:

0.164-32 unc

Fsc Application Data:

Early warning set, guided missile defense system

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100