NSN 5999-00-078-3232

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-078-3232

inread Class:
2b
Thread Pitch Diameters:
+0.1875 to 0.1876 inches
Body Style:
Rectangular
Frequency Rating:
13.000 kilohertz
Body Length:
7.500 inches
Body Width:
1.343 inches
Individual Section Quantity:
1
Operating Tempurature Range:
-55.0 to 105.0 degrees celsius
Mounting Facility Quantity:
6
Material And Location:
Any acceptable
Surface Treatment And Location:
Enamel, mil-e-15090, type 1, class 2 case
Input Impedance Rating:
600.000 ohms
Output Impedance Rating:
600.000 ohms
Body Depth:
2.156 inches
Mounting Facility:
Threaded hole
Attenuation In Decibels:
3.000
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
61.600 microseconds single section
Segment Quantity Per Section:
3 single section
Segment Delay Time:
29.600 microseconds single section 3rd segment

NSN 5999-00-078-3232

Delay Line - Page 2 of 2



Terminal Type And Quantity	Terminal	Type	And	Quantity	/ :
----------------------------	----------	-------------	-----	----------	------------

5 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Sonar detecting-ranging set

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100