

View Online at <https://aerobasegroup.com/nsn/5999-00-081-0305>

Thread Class:

2a

Body Style:

Rectangular

Body Length:

4.250 inches

Body Width:

1.875 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.125 inches

Longest Vertical Distance Between Mounting Centers:

1.375 inches

Operating Temperature Range:

-55.0 to 125.0 degrees celsius

Stud Length:

0.500 inches

Mounting Facility Quantity:

4

Material And Location:

Steel case

Surface Treatment And Location:

Enamel, mil-e-15090, class 2 case

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

10.000 ohms

Frequency Bandwidth:

2400.0 kilohertz

Body Depth:

1.625 inches

Mounting Facility:

Threaded stud

Attenuation In Decibels:

3.000

Signal Delay Method:

Lumped constant

Section Delay Time:

5.000 microseconds single section

Segment Quantity Per Section:

1 single section

Delay Time Variation Per Deg Celsius:

5.000 microseconds

Pulse Rise Time Rating:

0.2 microseconds

Terminal Type And Quantity:

3 tab solder lug

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100