NSN 5999-00-083-3093

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-083-3093

| Body Style: |
|---|
| Rectangular, bracketed |
| Hole Diameter: |
| Between 0.196 inches and 0.203 inches |
| Overall Length: |
| 4.390 inches |
| Body Length: |
| 3.062 inches |
| Body Width: |
| 0.797 inches |
| Individual Section Quantity: |
| 1 |
| Longest Horizontal Distance Between Mounting Centers: |
| 3.880 inches |
| Operating Tempurature Range: |
| +0.0 to 85.0 degrees celsius |
| Mounting Facility Quantity: |
| 2 |
| Voltage Rating: |
| 30.000 volts |
| Material And Location: |
| Metal |
| Surface Treatment And Location: |
| Enamel, gray |
| Input Impedance Rating: |
| 1.000 kilohms |
| Output Impedance Rating: |
| 1.000 kilohms |
| Body Depth: |
| 0.797 inches |
| Mounting Facility: |
| Unthreaded hole |
| Mounting Provision Arrangement Style: |
| 2 position in-line |
| Signal Delay Method: |
| Lumped constant |
| Delay Time Variation Method: |
| Tapped |
| Section Delay Time: |
| 7.500 microseconds single section |
| Segment Quantity Per Section: |
| 4 single section |

NSN 5999-00-083-3093

Delay Line - Page 2 of 2



3.000 microseconds single section 4th segment

Terminal Type And Quantity:

7 tab solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32100