

View Online at <https://aerobasegroup.com/nsn/5999-00-104-9971>

**Overall Length:**

Between 1.539 inches and 1.569 inches

**Overall Diameter:**

Between 0.296 inches and 0.302 inches

**Voltage Rating In Volts:**

400.0 ac

**Mounting Method:**

Force fit

**Material:**

Plastic fluorinated ethylene propylene barrel insulation

**Material Specification:**

Qq-b-626, comp 22, 1/2 hard federal specification single material response body and contact

**Precious Material And Location:**

Body and contact surfaces gold and body and contact surfaces silver

**Precious Material And Weight:**

0.005 gold grains, troy and 0.005 silver grains, troy

**Precious Material:**

Gold and silver

**Surface Treatment:**

Gold and silver body and contact

**Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response and qq-s-365 federal specification 2nd treatment response body and contact

**Style Designator:**

Cylindrical shape

**Test Data Document:**

24930-g260001-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

1 solder well axially at one end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A222a0

**Mil-std (military Standard):**

Mil-g-45204 spec.