NSN 5999-00-106-1225



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-106-1225 **Thread Class:** 2b **Thread Pitch Diameters:** +0.0960 to 0.0990 inches **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 4.750 inches **Body Width:** 3.125 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 4.125 inches **Operating Tempurature Range:** -46.0 to 85.0 degrees celsius **Mounting Facility Quantity: Voltage Rating:** 10.000 volts **Material And Location:** Plastic, I-p-403, type 1, class 1 body Input Impedance Rating: 1.500 kilohms **Output Impedance Rating:** 1.500 kilohms Frequency Bandwidth: Not rated **Body Depth:** 0.570 inches **Mounting Facility:**

Threaded hole **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** 4.000 **Signal Delay Method:** Transmission line

Delay Time Variation Method:

Variable

NSN 5999-00-106-1225

Delay Line - Page 2 of 2



Section Delay Time:
33.900 microseconds single section
Segment Quantity Per Section:
4 single section
Segment Delay Time:
8.000 microseconds single section 3rd segment
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
800.0 nanoseconds
Terminal Type And Quantity:
6 wire leads
Thread Size And Series/type Designator:
0.112-40 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

Fiig: A32100