NSN 5999-00-113-7459

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-113-7459

Thread Class:
2b
Thread Pitch Diameters:
+0.0813/+0.0958 inches
Body Style:
Rectangular, front connection
Overall Depth:
1.030 inches
Shaft Length:
0.750 inches
Adjustment Device Quantity:
1
Adjustment Device Drive Type:
Shaft
Body Length:
3.500 inches
Body Width:
1.000 inches
Shaft Style:
Round, slotted
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
3.100 inches
Operating Tempurature Range:
+0.0/+85.0 degrees celsius
Inclosure Type:
Encased
Mounting Facility Quantity:
2
Voltage Rating:
25.000 volts
Material And Location:
Aluminum body
Surface Treatment And Location:
Cadmium plated terminal
Input Impedance Rating:
200.000 ohms
Output Impedance Rating:
200.000 ohms
Body Depth:
0.750 inches

NSN 5999-00-113-7459

Delay Line - Page 2 of 2



Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

1.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

Section Delay Time:

100.000 nanoseconds single section

Pulse Rise Time Rating:

15.0 nanoseconds

Terminal Type And Quantity:

4 pin

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100