NSN 5999-00-116-7366

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-116-7366

View Online at https://aerobasegroup.com/nsn/5999-00
Thread Class:
2a
Thread Pitch Diameters:
+0.2500/+0.2501 inches
Body Style:
Rectangular
Body Length:
11.500 inches
Body Width:
3.500 inches
Individual Section Quantity:
1
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Stud Length:
0.470 inches
Mounting Facility Quantity:
8
Material And Location:
Any acceptable
Surface Treatment And Location:
Any acceptable
Input Impedance Rating:
1.000 kilohms
Output Impedance Rating:
1.000 kilohms
Body Depth:
4.000 inches
Mounting Facility:
Threaded stud
Attenuation In Decibels:
4.000
Signal Delay Method:
Inductance
Delay Time Variation Method:
Tapped
Section Delay Time:
2900.000 milliseconds single section
Segment Quantity Per Section:
29 single section
Segment Delay Time:
100.000 milliseconds single section all segments
Ç Ç

NSN 5999-00-116-7366

Delay Line - Page 2 of 2



Terminal Type And Quantity:

28 tab solder lug

Thread Size And Series/type Designator:

0.164-32 unc

Fsc Application Data:

Radio except navigation nonairborne

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100