NSN 5999-00-131-6697



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-131-6697 **Thread Class:** 2b **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 2.500 inches **Body Width:** 0.400 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.000 inches **Longest Vertical Distance Between Mounting Centers:** 2.000 inches **Operating Tempurature Range:** -40.0 to 80.0 degrees celsius **Mounting Facility Quantity: Voltage Rating:** Not rated **Material And Location:** Any acceptable **Surface Treatment And Location:** Any acceptable Input Impedance Rating: 1.800 kilohms **Output Impedance Rating:** 1.800 kilohms Frequency Bandwidth: 1200.0 kilohertz **Body Depth:** 1.400 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** 2 position diagonal

Attenuation In Decibels: 1.000

Signal Delay Method:

Inductance

NSN 5999-00-131-6697

Delay Line - Page 2 of 2



Section	Delay	Time:
---------	-------	-------

3.000 microseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

0.3 microseconds

Terminal Type And Quantity:

3 pin

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radio navigation, nonairborne

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100