

View Online at <https://aerobasegroup.com/nsn/5999-00-139-5976>

Thread Class:

2b

Body Style:

Rectangular

Slot Depth:

Any acceptable

Slot Width:

Any acceptable

Shaft Diameter:

0.187 inches

Shaft Length:

0.060 inches

Frequency Rating:

5.000 kilohertz

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Shaft

Body Length:

1.250 inches

Body Width:

1.030 inches

Shaft Style:

Round, slotted

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.000 inches

Longest Vertical Distance Between Mounting Centers:

0.800 inches

Operating Temperature Range:

-54.0 to 110.0 degrees celsius

Mounting Facility Quantity:

2

Voltage Rating:

12.000 volts

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

93.000 ohms

Output Impedance Rating:

2.000 kilohms

Frequency Bandwidth:

7000.0 kilohertz

Body Depth:

0.310 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

2 position diagonal

Attenuation In Decibels:

Not rated

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Variable

Section Delay Time:

110.000 nanoseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

10.0 nanoseconds

Terminal Type And Quantity:

4 pin

Thread Size And Series/type Designator:

0.086-56 unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100